



Odi Touch

Chemical Dosing System

Odi Touch

Chemical Dosing System

ODI Touch is an automated chemical control system for domestic and commercial pools and spas. It provides options for monitoring free or active chlorine, pH, and temperature, and can also measure total chlorine, conductivity, and more. With touchscreen operation and remote monitoring available, it is suitable for indoor and outdoor pool and spa applications that require reliable chemical dosing control.



Key Benefits

- Intuitive touch-screen controller
- 8 inputs with additional sensors available to monitor Free, Active, Total and Combined Chlorine, pH, Temperature, Conductivity, Turbidity, and filter pressure
- 10 installer-programmable outputs across 230VAC, volt-free and digital to automate liquid chlorine backup for salt chlorination, auto CO2/Acid changeover, temperature control, etc
- User-friendly interface with adaptable configurations for various pool volumes and actions
- Dosing stops on high/low alarms, with programmable maximum daily dosing time
- Compatible with all chlorine types: stabilised chlorine, liquid chlorine, salt chlorination, pellets
- Versatile multi-parameter control
- Continuous self-diagnosis for optimal efficiency
- Various regulation types: PID (cycle or pulse), on/off, threshold, hysteresis

Applications

Odi Touch is suitable for a wide range of domestic and commercial aquatic facilities, including:

- Residential pools and spas
- Apartments and retirement villages
- Hotels and resorts
- Healthcare facilities
- Learn-to-swim schools and educational facilities
- Public aquatic centres
- Government and community facilities
- Fitness and wellness centres



Models

Code	Description
ODIA	Active chlorine, pH, and temperature sensors. Suitable for indoor pools or spas with bromine, chlorine (all types), or salt chlorination. Indoor pool or spa Cyanuric acid MUST BE 0ppm or less than 2ppm. Compatible with by-products of electrolysis (salt chlorination). Complete with pH & chlorine output.
ODIAT	Active chlorine, Total chlorine, pH, and temperature sensors. Suitable for indoor pools or spas with bromine, chlorine (all types). Indoor pool or spa Cyanuric acid MUST BE 0ppm or less than 2ppm. Complete with pH & chlorine output.
ODIATS	Active chlorine, Total chlorine, pH, and temperature sensors. Suitable for indoor pools or spas with bromine, chlorine (all types), or salt chlorination. Indoor pool or spa Cyanuric acid MUST BE 0ppm or less than 2ppm. Compatible with by-products of electrolysis (salt chlorination). Complete with pH & chlorine output.
ODIF	Free chlorine, pH, and temperature sensors. Outdoor pools or spas Cyanuric acid MUST BE 20-40ppm. Compatible with by-products of electrolysis (salt chlorination). Complete with pH & chlorine output.
ODIFT	Free chlorine, Total chlorine, pH, and temperature sensors. Outdoor pools or spas Cyanuric acid MUST BE 20-40ppm. Not suitable for by-products of electrolysis (salt chlorination). Complete with pH & chlorine output.
ODIFTS	Free chlorine, Total chlorine, pH, and temperature sensors. Outdoor pools or spas Cyanuric acid MUST BE 20-40ppm. Compatible with by-products of electrolysis (salt chlorination). Complete with pH & chlorine output.



System Compatibility

This system is compatible with most swimming pool systems. Integration support available via Waterlink's technical team.



Warranty

Waterlink systems are built for durability. This product is backed by our standard commercial warranty. For full warranty terms and coverage, please visit www.waterlink.com/warranty



Looking for More Solutions?

Hydro Touch

Hydro Touch pH & ORP Controllers. For both residential & commercial pools & spas up to 160,000 litres.

Tere'O Touch

Tere'o Touch is an automated chemical control system for domestic and commercial pools and spas. It provides options for monitoring free or active chlorine, pH, and more, with touchscreen operation and remote monitoring available. It is suitable for indoor and outdoor pool and spa applications that require reliable chemical dosing control. Tere'O Touch is available in two options.

Contact our team to receive a tailored quote:  1300 897 200  sales@waterlink.com



Need More Information?

If you're unsure about which product of our range is the right fit for your facility, our team is here to help.
Contact us for more details or to request a tailored recommendation.

 1300 897 200  sales@waterlink.com  www.waterlink.com

Waterlink Equipment Pty Ltd | Head Office: Factory 2, 40 Titan Drive Carrum Downs, VIC 3201 Australia

Last updated: 15/06/2026